- - -

\_ \_

.

## Supplement to The Belfast Gazette, 18th December, 1979

`..,

## SCHEDULE 13 (contd.)

## PART 2 (contd.)

		Rate of rental £	Maximum connection charge £
4.	System C		
	Call-out point equipment	7 · 50 6 · 25	. ]
	Additional call-out point equipment	7.50	No further connection of
	Ring-out point (with local siren and call bells)	12.00	these items will be made.
	Ring-out point (with remote siren and call bells)	15.50	
	Remote siren point equipment	3.50	
	Konoto bien point equipitante 17 11 11 11		2
5.	System K		
	Call-out point equipment per circuit	7.00	
	Ring-out point equipment (local siren)	10-50	
	Ring-out point equipment (remote siren)	14.00	No further connection of
	Remote siren point equipment	3.50	(these items will be made.
			J
	VP Contains 1		
6.	VF System A (a) Control station:		
	Equipment to control up to 5 remote stations	50.00	50.00
		12.00	20.00
	•	12.00	20.00
	(b) Power:	<u> </u>	40.00
	Basic unit for control station with only one system controlled Control station unit for:	28.50	40.00
	2-5 systems	45· <b>0</b> 0	40.00
	6-10 systems	52 · 50	50.00
	11–15 systems	63 • 75	50.00
	(c) Remote stations:		
	Equipment per station	62 · 50	80.00
	Basic power unit for each remote station	28.50	40.00
	"999" fire call termination	6.75	9.00
	Relay set	2.50	9.00
	Three relay sets on one base	7.00	9.00
		,	,
7.	Modifications at Remote Stations to allow use of Pocket Alerters:		
	(a) For connection to any of: (i) System AA	3.00	9.00
	(ii) System K (HO transmitter in same building as control unit)	3.00	9.00
	(iii) System K (HO transmitter in same building as control unit) (iii) System K (HO transmitter remote controlled AA; siren		9-00
	retained)	3.00	9.00
	(iv) System DX (HO transmitter in same building as ROP)	3.00	9.00
	(v) System DX (HO transmitter remote controlled AA; siren		
	retained)	3.00	9.00
	(vi) System VFA (HO transmitter in same building as VF		
	equipment)	3.00	9.00
	(vii) System VFA (HO transmitter remote controlled; siren		
	retained)	3.00	9.00
	(viii) System FVA (HO transmitter remote controlled; siren		
	not required)	3.00	9.00
	(ix) Telegraph Call-Out System	3.00	9.00
	(b) For connection to Systems AA, K and DX (HO transmitter		
	remote controlled; siren not required)	Nil	9.00
		7.50	9.00.".
	(c) Teleprinter Electronic Timer	1.30	<b>7</b> ° <b>W</b> .,