

SCHEDULE 17 (contd.)

	£ (Maximum)
20. HES: second main telephone apparatus	12·00
21. Optional HES facilities provided by modification of the existing installation:	
(a) small trembler bell for night service or alternative to second main telephone	12·00
(b) monitoring facilities	12·00
(c) station barring	12·00
(d) facility for calling main telephone when it is engaged on an exchange line call:	
(i) by modification of existing main telephone	12·00
(ii) by substitution of main telephone	12·00
(iii) permanent alarm on second main telephone apparatus	12·00
22. PMBX 4 (non-multiple):	
long cord kit: per position	250·00
23. Printing reperforator No. 5A: small instrument case	80·00
24. Non-standard dial centre labels	10·00
25. Telespot (Phone-in equipment for the broadcasting of live telephone calls); central equipment	250·00
26. Enlarged Numeral Dial Ring:	
where a special visit by a person engaged in the business of the Post Office is necessary	8·00
otherwise	1·00
27. Trolley for coinbox 725 (portable)	40·00
28. Remotely sited bell unit for use with Compact Telephone and Compact Telephone (Jubilee Year Version) when additional wiring is required	6·00
29. Self-contained press-button Trimphone	5·00
30. Self-contained press-button Telephone	5·00
31. Press-button Trimphone (other than self-contained)	5·00
32. Press-button Telephone (other than self-contained)	5·00
33. X-Press callmaker	5·00
34. Explosive Atmosphere Telephone with reference number in the 700 series	100·00
35. Out-of-Order panel on Post Office rented PABXs:	
charge per private circuit or exchange line connected on the Out-of-Order panel	22·50
36. Self-Adhesive Dial Ring	0·40
Para. 61	
37. Freefone telephone service	100·00
38. Cartridge for Answering Machine No. 3A	5·00
39. Herald Call Connect System:	
interfacing equipment per exchange line	35·00
40. Monarch 120 A1 Call Connect System:	
(a) interfacing equipment per exchange line	95·00
(b) alarm for power fail condition	120·00
(c) conference board (3 party)	185·00
(d) transparent doors	150·00
41. PABX type 1: Fitting of diode for discriminatory call barring:	
per extension	9·00."